

Mobile Precision in Metal Analysis



belec compact port hlc

Your reliable companion for mobile metal analysis. Robust, modern and unbeaten flexible. Ideal for laboratory and on-site use.

SAFE, FAST AND PRECISE

Up to 70 chemical elements in metals can be reliably detected in just a few seconds. Thanks to careful sample preparation, there is hardly an analysis task that it cannot master.

- Analysis of phosphorus (P) and sulfur (S) with the UV+ probe
- Analysis of nitrogen in duplex steels
- Mix-Up-Tests (PMI) in seconds with the air probe
- Analyze wires, pipes or small parts in a almost any variety of dimensions with our special adapters

YOUR ADVANTAGES AT A GLANCE:

- LIGHT WEIGHT AND PORTABLE
 Sturdy trolley offers mobility and stability and storage space for accessories.
- **ERGONOMIC SPARKING PROBES** Flexible optical fibre up to 8 m length.
- BATTERY POWER SUPPLY OPERATION POSSIBLE

Powerful battery for mobile use.

• **EASY TO USE**Intuitive touchscreen – fast and user-friendly.





Sparking probe featuresUV+ probeArgon probeAir probeArgon-flushed sparking probe incl. C-analysis•-Argon-flushed sparking probe incl. P, S, N*-analysis•-Probe connector system••Quick mix-up checking--Multi fibre quartz optics, 3 m to 8 m*••Adapters for tubes, wires + small parts••Non-destructive material testing••

FLEXIBLE SOLUTIONS FOR ANY PROBE

With our specially designed adapters, you can easily analyze even challenging samples such as wires, pipes or small parts. We also offer individual additional solutions that make your work easier and improve the results.























DIN EN ISO 9001 **REG.-NR.** Q1 0310014

V125/Technical changes reserved/*optional

TECHNICAL SPECIFICATIONS

Optics

- Spectrometer in Paschen-Runge mounting
- Rowland circle diameter 300 mm
- Usable wavelengths 145-410 nm
- Zeiss grating with 3600 groves/mm
- · Reciprocal dispersion 0.9 nm/mm
- Shock-resistant
- Temperature-stabilized detectors

Sparking probes

- Argon-flushed probe for precise analysis including C, P, S, N
- Air probe for quick mix-up tests
- Adapter for wires, pipes and small parts available for all probes
- · Multi-fibre quartz light fibre
- Standard length 3 m (up to max. 8 m)
- No-wear tungsten electrode
- Configurable spark parameters
- · Optional arc excitation

Dimensions/weights

- 420 x 200 x 490 mm/16.5 x 7.87 x 19,3 in (WxHxL)
- Analyzer 23.00 kg (50.7 lb)
- UV+ probe 1.75 kg (3.85 lb)
- Argon probe 1.30 kg (2.86 lb)
- Air probe 0.80 kg (1.76 lb)

Electrical specifications

- 230V/50Hz or 110V/60Hz
- 70W standby
- 550W analysis

Computer hardware

- · System-integrated industrial computer
- Minimum 250 GB SSD
- Touch display
- · Industrial keyboard in protective lid
- USB ports
- Ethernet port

THE MOBILE SPECTROMETER FOR EVERY APPLICATION

Ideal for workshops, construction sites, scrap yards and much more. Contact us!

Belec Spektrometrie Opto-Elektronik GmbH

Hamburger Str. 12, 49124 Georgsmarienhütte Germany

Fon +49 5401 8709-0 Mail info@belec.de Web www.belec.de

